



DRIVING SURFACE PERFECTION

# RAPTOR 1K MULTI USE PROTECTIVE COATING AEROSOL

RMUB/AL

Version: 4.0

Date of issue: 22/06/2018 Revision date: 30/03/2021 Supersedes: 22/03/2020



## TECHNICAL DATASHEET

RAPTOR Multi-Use Protective Coating protects a variety of surfaces from impact, scratches, corrosion and water damage. Ideal for vehicles, trailers, railings, stairs, metal furniture and more... Its 1K formulation gives a durable, abrasion resistant finish with excellent adhesion to metal, aluminium, fiberglass, plastic and wood. Clog free nozzle and easy to use, it dries to form an attractive, textured finish that resists fading from the sun.

- Textured finish.
- Durable and gives good corrosion resistance.
- Excellent adhesion to prepared metal, aluminium, fiberglass, plastic and wood.

Product	Order Code	Format	Shelf Life
RAPTOR 1K MULTI USE PROTECTIVE COATING AEROSOL	RMUB/AL	450ml Aerosol	5 years

## APPLICATION INFORMATION



FOR PPE RECOMMENDATIONS REFER TO SDS

**IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.** This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information.



### Surface Preparation



#### Substrate

Bare Steel\*  
Aluminium\*  
Galvanised\*  
Prepared OEM surfaces  
SMC, Fibreglass  
Lightly abraded E-Coat  
Most Plastics\*\*  
Wood

#### Degreaser

SYSTEM 20 Solvent-Based Degreaser  
SYSTEM 20 Solvent-Based Degreaser  
SYSTEM 20 Solvent-Based Degreaser  
SYSTEM 20 Solvent-Based Degreaser  
SYSTEM 20 Water-Based Degreaser  
SYSTEM 20 Solvent-Based Degreaser  
SYSTEM 20 Water-Based Degreaser  
Not required

#### Abrasion

P80 - P120  
P120  
P120  
P80 - P120  
P80 - P120  
Not required  
P120  
Not required

For best results, good preparation is essential. Clean and degrease removing dirt, oil, grease and wax using cleaning solutions such as U-POL's SYSTEM 20 Degreasers. Abrade with grit paper as stated above for each respective substrate. Re-clean, dry and degrease the abraded substrate ready for application. \*For optimum results, apply 1-2 light even coats of RAPTOR Acid Etch Primer, allowing 20 minutes drying time before application. \*\*Plastics should be treated with an adhesion promoter such as RAPTOR Adhesion Promoter Aerosol. PLEASE NOTE: this product is not recommended for application over thermoplastic acrylics.

### Mixing



Shake the aerosol can for at least 2 minutes before use.

### Number of Coats



#### Distance from the surface

30 cm / 12 inches

#### Application Temperature

20 °C / 70 °F

#### Coats

1 - 2

#### Flash-off at 20°C

10 – 15 minutes between coats

#### Total Dry Film Thickness

110 – 140 µm (4.3 - 5.5 MIL)

#### Theoretical Coverage @ indicated DFT\*

0.8 – 1 m<sup>2</sup>/unit

\*Theoretical Coverage per unit assuming 100% transfer efficiency and giving the dry film thickness at the indicated values.

### Drying Time



PLEASE NOTE: drying times are dependent upon film thickness, humidity and temperature.

#### Touch Dry at 20°C

&lt; 60 minutes

#### Dry-Through at 20°C

3 – 4 hours

### Overpainting



This formulation can be directly overcoated without sanding with most water/solvent-based paint systems.

#### Overcoatable at 20°C after

3 – 4 hours

## TECHNICAL INFORMATION

### Physical properties



#### Appearance

Aerosol.

#### Colour

Black

#### Density

0.96 g/cm<sup>3</sup>

#### Percent Solids

30.29 wt%



DRIVING SURFACE PERFECTION

# RAPTOR 1K MULTI USE PROTECTIVE COATING AEROSOL

RMUB/AL

Version: 4.0

Date of issue: 22/06/2018 Revision date: 30/03/2021 Supersedes: 22/03/2020



## TECHNICAL DATASHEET

### VOC Information



The VOC content of this product as received is 579 g/l. The VOC content of this product in ready to use form is 579 g/l.

### Storage



Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximise the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

**Recommended storage temperature** 5 °C - 25 °C

### Associated Products



#### Product

SYSTEM 20 Water-Based Degreaser  
 SYSTEM 20 Solvent-Based Fast Degreaser  
 SYSTEM 20 Solvent-Based Slow Degreaser  
 SYSTEM 20 Solvent-Based Slow Degreaser  
 WIPE #6 Solvent-Based Degreaser Aerosol  
 RAPTOR Acid Etch Primer Aerosol  
 RAPTOR Adhesion Promoter Aerosol  
 MAXIMUM Professional Lint-Free Solvent Wipes  
 MAXIMUM Tack Cloths  
 MAXIMUM Tack Cloths  
 MAXIMUM Premium Masks  
 MAXIMUM Painters Overalls  
 MAXIMUM Painters Overalls  
 MAXIMUM Painters Overalls  
 MAXIMUM Painters Overalls  
 MAXIMUM Painters Overalls  
 MAXIMUM Abrasive Latex Paper Discs P80  
 MAXIMUM Abrasive Latex Paper Discs P120

#### Order Code

S2000/5 5L Canister  
 S2001/5 5L Tin  
 S2002/1 1L Tin  
 S2002/5 5L Tin  
 WIPE/AL 450ml Aerosol  
 RPTEP/AL 450ml Aerosol  
 RPTAP/AL 450ml Aerosol  
 MWPP/350 100-pack  
 TRAG/10 10-pack  
 TRAG/50 50-pack  
 RESPV 1-pack  
 COVER/M 1-pack  
 COVER/L 1-pack  
 COVER/XL 1-pack  
 COVER/XXL 1-pack  
 COVER/XXXL 1-pack  
 ABD7/VP80 100-pack  
 ABD7/VP120 100-pack

#### Format

U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits. U-POL is not liable for mis-use or abuse of its products and no application warranty is expressed or implied.

For additional technical assistance, please contact the U-POL Technical Department at [technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com)

U-POL Australia Pty Limited  
 Unit A, 16 - 20 Cassola Place  
 NSW 2750 Penrith - Australia  
 T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.co.au](mailto:info@u-pol.co.au) - [www.u-pol.com](http://www.u-pol.com)

U-POL New Zealand Limited  
 c/o Lindsay & Associates  
 Unit H, 12 Amera Place, East Tamaki  
 2013 Manukau City - New Zealand  
 T + 612 4731 2655 - F + 612 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com](http://www.u-pol.com)